

























2 MEGA PIXEL IP CAMERA SERIES				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
VNC-2221		2MP	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), 2.8mm & 4mm Lens, H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): plastic	9,900,000
VNC-2261		2MP	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, IK10, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Base bracket: metal Cover: plastic	10,500,000
VNC-5225N		2MP	1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter Ultra-low light technology, Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); 2.8/4/6mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, , Smart Series	CALL
VNC-5265		2MP	1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter Ultra-low light technology, Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); 2.8/4/6mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, , Smart Series	CALL
3 MEGA PIXEL IP CAMERA SERIES				
VNC-2321		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): Metal Back cover & Bracket(white part): plastic	CALL
VNC-2361		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Eyeball: Metal Cover: Plastic	CALL
VNC-2331		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8~12mm Vari-Focal lens, H.264+&H.264, IP67, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
VNC-2371		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, IK10, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
www.didafzar.ir / sales@didafzar.ir / Mobile support: 09011771631 / Tel: 02188662211 / Address: No3 3rd Floor Sadaf BLG Valiasr Ave. Tehran				

4 MEGA PIXEL IP CAMERA SERIES				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
VNC-2421		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): plastic	15,600,000
VNC-2461		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Eyeball: Metal, Cover: Plastic	15,600,000
VNC4423		4MP	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, cloud P2P, H.264+ Optimized Codec-I5: 2pcs EXIR LEDs, up to 50m IR range	CALL
VNC-2431		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
VNC-4430		4MP	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm Vari-Focal lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ Optimized Codec, Professional Series	CALL
VNC-2471		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, IK10, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal	CALL
5 MEGA PIXEL SMART IP CAMERA SERIES				
VNC-5525N		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux, 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8/4/6/12mm lens optional; 120dB WDR; VCA functions ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; SD/SDHC/SDXC slot, up to 80m IR distance , Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Smart Series	CALL
VNC-5535SN		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux, 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8~12mm motorized VF lens; 120dB WDR; VCA functions ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 50m IR distance; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, S model: Audio/Alarm IO, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Smart Series	CALL
VNC-5575SN		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@ (F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8~12mm motorized VF lens; 120dB WDR; VCA functions ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67, IK8; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, S model: Audio/Alarm IO, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Smart Series	CALL
www.didafzar.ir / sales@didafzar.ir / Mobile support: 09011771631 / Tel: 02188662211 / Address: No3 3rd Floor Sadaf BLG Valiasr Ave. Tehran				

4K IP CAMERA SERIES				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
VNC-5826		8MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (2560x1920, 2560x1440, 2048x1536, 1920x1080); 2.8/4/6/12mm lens optional; 120dB WDR; VCA functions ; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, up to 80m IR distance , Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, 4K smart Camera	CALL
1 MEGA PIXEL PINHOLE IP CAMERA				
VNC-4190		1MP	1/4" Progressive CMOS, H.264, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC,	16,500,000
4MEGA PIXEL CUBE IP CAMERA				
VNC-1490		4MP	1/3" Progressive CMOS, H.264+, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB(SD card not included), built-in WIFI, H.264+ Optimized Codec	19,000,000
6MEGA PIXEL FISH EYE IP CAMERA				
VNC-6640S		6MP	1/2" Progressive CMOS, H.264, Fish eye, ICR, 0lux with IR, Up to 3072 x 2048 resolution, 1.05mm/F2.8 lens, 360° Panoramic view, H.264/MJPEG, dual-stream, DC12V & PoE, Support on-board storage, Up to 15m IR, Audio/Alarm IO	CALL
2 MEGA PIXEL ANPR IP CAMERA				
VNC-6225S		2MP	License Plate Recognition, Darkfighter ultra-low light technology, 1/1.8" progressive scan CMOS sensor, Full HD1080p, up to 60fps, 120dB WDR, Full smart feature-set, Motorized lens with Smart Focus, Up to 128GB on-board storage, Up to 50m IR range, IP67	CALL
VNC-6226S		2MP	License Plate Recognition, Darkfighter ultra-low light technology, 1/1.8" progressive scan CMOS sensor, Full HD1080p, up to 60fps, 120dB WDR, Full smart feature-set, Visible Light, Motorized lens with Smart Focus, Up to 128GB on-board storage, Up to 50m IR range, IP67	CALL
2 MEGA PIXEL SMART IP CAMERA				
VNC-5230		2MP	Darkfighter Ultra-low light technology, 1/1.8" Progressive Scan CMOS, ICR, 0 lux with IR, Slow shutter, 1920x1080: 50/60fps, 2.8-12mm/F1.4 Motorized VF lens with Smart Focus, H.264/MPEG4, Triple-Stream, Support SD/SDXC Card up to 128GB, IP67, DC12V/PoE, up to 50m IR range, Bracket & junction box included, - S: Audio/Alarm IO, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Poepple count, , Smart Series	CALL









SPEED DOME IP CAMERA SERIES				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
VNC-2280N		2MP	2MP, 1/3" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.05lux/F2.0, B/W:0.01lux/F2.0, Zoom: 4x, Angle of View: 80-64.5 degree (Wide~Tele), Digital Zoom:16X, 1920x1080:30fps, Pan range:0°~350°; Tilt range: 0°~90°(Auto Flip), Pan Speed: 0.1° -100°/s, Tilt Speed: 0.1° -80°/s, 30m IR, POE&12VDC,	CALL
VNC-2281N		2MP	2MP, 1/3" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance	CALL
VNC-4285N		2MP	2MP, 1/2.8" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:12X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 120m IR Distance	CALL
VNC-5880		8MP	8MP PTZ , 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:36x, Focus:4.3-129.0mm, Digital Zoom:12X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 200m IR Distance	CALL
VNC-6280		16MP	16MP PTZ , 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:36x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance	CALL
ACCESSORIES				
MODEL	PICTURE	FEATURES	DESCRIPTION	PRICE
VHN-K130		Multi	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup, 256 units of DVR and SeedDome	CALL
VCU-1200		Multi	<ul style="list-style-type: none"> Control up to 255 PTZ cameras Superior system compatibility : Multi protocols support OSD menu • 3D joystick control Control up to 255 PTZ cameras 	36,000,000
VPS-8100		1.8 Gbps switching fabric	IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant , Supports PoE power up to 123W for all PoE ports (8 port) and 230W for (16 port) ,4 kV surge protection for PoE ports , IEEE 802.3x flow control support , Plug-and-play installation , 1.8 Gbps switching fabric (8 port) and 7.2 Gbps switching fabric , 1.25 & 2.75 Mbits RAM Data Buffer , Sturdy metal enclosure, 30 watts per PoE	CALL
VPS-16100		7.2 Gbps switching fabric		CALL
VPS-24100		8.8 Gbps switching fabric		CALL
www.didafzar.ir / sales@didafzar.ir / Mobile support: 09011771631 / Tel: 02188662211 / Address: No3 3rd Floor Sadaf BLG Valiasr Ave. Tehran				



EMPOWERED BY INNOVATION
TURBO HD SOLUTION PRICE LIST

نماینده انحصاری محصولات حفاظتی ورتینا در ایران

لیست قیمت تجهیزات حفاظتی تحت شبکه ورتینا








4 CHANNEL NETWORK VIDEO RECORDER			
MODEL	PICTURE	DESCRIPTION	PRICE
VNR-405		40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay,packet loss, etc	12,900,000
VNR-405P		40Mbps Bit Rate Input Max (up to 4-ch IP video), 2 SATA interfaces, 4 independent network POE interfaces for built-in switch, 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	24,800,000
8 CHANNEL NETWORK VIDEO RECORDER			
VNR-805		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	22,600,000
VNR-805E		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent network interfaces for built-in switch, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	30,000,000
VNR-805P		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent network POE interfaces for built-in switch, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	36,000,000
VNR-808		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 8 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	23,900,000
16 CHANNEL NETWORK VIDEO RECORDER			
VNR-1605		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	25,500,000
VNR-1605E		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent network interfaces for built-in switch, 380 1U case , Third-party network cameras supported , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	44,500,000



EMPOWERED BY INNOVATION
TURBO HD SOLUTION PRICE LIST

نماینده انحصاری محصولات حفاظتی ورتینا در ایران

لیست قیمت تجهیزات حفاظتی تحت شبکه ورتینا

16 CHANNEL NETWORK VIDEO RECORDER			
MODEL	PICTURE	DESCRIPTION	PRICE
VNR-1605P		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent network POE interfaces for built-in switch, 380 1U case , Third-party network cameras supported , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	48,700,000
VNR-1608		160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 8 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	28,300,000
VNR-1612 P4		160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19" 4K resolution(up to 12MP), H.265/H.264+/H.264 supported	CALL
32 / 64 CHANNEL NETWORK VIDEO RECORDER			
VNR-3212 P4		256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 2U case,19" 4K resolution(up to 12MP), H.265/H.264+/H.264 supported	CALL
VNR-3212P16		Third-party network cameras supported , Up to 12 Megapixels resolution recording , Support 2-ch HDMI, 2-ch VGA, HMDI1 at up to 4K(3840x2160) , 2 RJ 45 1000M, Up to 32 IP cameras can be connected with 320M incoming bandwidth , Up to 16 SATA interfaces Support HDD hot swap with RAID0,1,5,6,10 storage , scheme configurable , Support various VCA detection alarm and VCA earch ,Support H.265/H.264/MPEG4 video formats, RAID0, RAID1, RAID5, RAID6, RAID10	CALL
VNR-6412P16		Third-party network cameras supported , Up to 12 Megapixels resolution recording , Support 2-ch HDMI, 2-ch VGA, HMDI1 at up to 4K(3840x2160) , 2 RJ 45 1000M, Up to 64 IP cameras can be connected with 320M incoming bandwidth , Up to 16 SATA interfaces Support HDD hot swap with RAID0,1,5,6,10 storage , scheme configurable , Support various VCA detection alarm and VCA earch ,Support H.265/H.264/MPEG4 video formats, RAID0, RAID1, RAID5, RAID6, RAID10	CALL
Vertia 3500+ ServerStation		<ul style="list-style-type: none"> • 32 Channel connected cameras • Central management system • Supports GPU hardware decoding to save CPU resources • Windows Embedded System 7 • Storage 4 HDDs connectable • Third-party product integration via ONVIF • Decoding performance 2*4K / 9 * 1080p 	CALL
www.didafzar.ir / sales@didafzar.ir / Mobile support: 09011771631 / Tel: 02188662211 / Address: No3 3rd Floor Sadaf BLG Valiasr Ave. Tehran			